Video Conferencing System VC4

The TRIUMPH BOARD Video Conferencing System VC4 provides uniquely budget-friendly, 4-site, high-performance MCU, real-time full HD video streaming and HD real-time content sharing with recording capability.

Wide-angle Full HD camera with 16x optical zoom ensures no one is left out of the shot, a sophisticated audio processing technology microphone array produces true-to-life sound, a sleek and a compact system design enables easy integration with TRIUMPH BOARD LED LCD Series for an advanced total solution.

Features

- 4- Site System
- License upgrade to 6, 8 or 10 points
- · Full HD video & HD content sharing
- Easy connection set up
- One-touch recording



- High definition (+/- 100° pan, +/- 25° tilt) camera
- High-efficiency lost packet recovery technology
- · Microphone array advanced audio processing technology
- Software add-ons: TRIUMPH Meeting, TRIUMPH Link, TRIUMPH Share, TRIUMPH Player, WebTool application



TRIUMPH Meeting



TRIUMPH Link



TRIUMPH Share



TRIUMPH Player



WebTool application

TRIUMPH Meeting- mobility software to connect to desktops, laptops, tablets and mobile phones

TRIUMPH Link – share live images and snapshots directly from your mobile device

TRIUMPH Share - wirelessly share content from your PC at any time during a call

TRIUMPH Player - playback recorded meetings or convert the video files to a different format

WebTool application - handy integration remote access tools





Tel.: +420 224 610 221 Fax.: +420 224 910 218



Specifications

EAN:	8592580083150	Aud
Model:	TRIUMH BOARD Video Conferencing System VC4	Othe
Accessories in the box:	Main system unit (codec), PTZ HD camera, microphone array, IR remote control with batteries, power supply, cables, warranty card, quick installation card	Use
Communications:	H.323 and SIP standards, SIP TLS	
	64Kbps~4Mbps	
	RJ45 network LAN (10/100/1000)	
	Manual bandwidth settings	Netw
	Content sharing capability from all sites	
Camera:	Support for single camera	Sec
	pan/tilt/zoom camera	
	2-megapixel CMOS sensor	
	16x optical zoom; ±100° pan; ±25° tilt	Web
	FOV 61° (H); 35° (V); 67° (Diagonal)	1100
People video resolutions:	HD1080p (1920 x 1080)	Valu
	HD720p (1280 x 720)	
	480p (848 x 480)	
	4CIF (704 x 576)	
	CIF (352 x 288)	
	SIF (352 x 240)	
	All resolutions at 30fps	
Supported Content video resolutions:	HD1080p (1920 x 1080)	
	WSXGA+ (1680 x 1050)	Pow
	SXGA (1280 x 1024)	Envi
	WXGA (1280 x 768)	
	HD720p (1280 x 720)	Gros
	XGA (1024 x 768)	Dim
	SVGA (800 x 600)	
	D1 (720 x 480)	
	VGA (640 x 480)	
	Output resolutions: HD1080p (1920 x 1080) up to 30fps	Mob
Video standards:	H.264, H.264 HP, H.264 SVC, H.263+, H.263, H.261	
	H.239 dual video streams, BFCP content sharing	
Video inputs:	HD camera, VGA, DVI (HDMI)	
Video outputs:	HDMI, VGA	Opti
Audio standards:	G.711, G.722, G.722.1, G.728, G.722.1C	
Audio features:	Automatic gain control (AGC)	
	Advanced noise reduction	
	Acoustic echo cancellation (AEC)	
Audio inputs:	Microphone daisy chain up to 4	

Audio outputs:	HDMI, Line-out (0.138")
Other supported standards:	H.224, H.225, H.245, H.281, H.323 Annex Q, H.460
User interface:	Supports single and dual monitor display
	Multiple layout styles; Display / edit site name
	User-friendly OSD (27 supported languages: English, Czech, Danish, Arabic, Bulgarian, Croatian, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Latvian, Norwegian, Polish, Portuguese-Brazil, Romanian, Russian, Serbian, Slovak, Slovenian, Spanish, Swedish, Turkish, Ukrainian)
Network:	10/100/1000 Mbps; NAT / firewall traversal; High Efficiency Lost Packet Recovery (HELPeR™); API support via Telnet; Wake-on-LAN (WOL) support; IPv4 and IPv6 support; Network Test; QoS
Security:	AES (Advanced Encryption Standard) function (128-bit)
	Password protection for system settings
	Password protection for remote system management
Web management tool:	Remote management; Live monitoring; Firmware update; Phonebook download / upload / edit; Restore system settings
Value-added features:	Meeting recording: In meeting and offline recording, Save directly to USB flash drive, Supports screen re-layout during playback, Playback and file conversion via TRIUMPH Player software (.mov/.mp4 format)
	Speed dialing via hot keys (10 sets)
	Camera presets (10 positions)
	Network Time Protocol (NTP)
	License upgrade to 6, 8, 10 points
	TRIUMPH Share support
	TRIUMPH Link support
Power supply:	AC 100V~240V, 50/60Hz; Consumption: EIAJ 12V, 4A
Environmental data:	Operation temperature: 0~40°C; Operation humidity: 20%~80%
	Storage temperature: -20~60°C; Storage humidity: 20%~80%
Gross weight:	13.19 lbs
Dimensions:	Package: 14.88" x 11.69" x 8.82"
	Main system (codec): 12.60" x 10.34" x 1,46"
	Camera: 4.82" x 4.82" x 6.28"
	Microphone array: 5.19" x 4.70" x 1"
Mobility Software:	Supported devices: Windows [®] and Mac OS [®] , iOS, Android phones and tablets, Windows 8 tablets
	Other features: Connect with H.264 and H.263+, Receive resolution up to HD 720p 30fps, Transmit resolution up to VGA 30fps, Compatible with VC1/VC4, Support content sharing
Optional accessories:	



Hardware specifications







