
## 84" MULTI Touch LED LCD



TRIUMPH BOARD 84" MULTI Touch LED LCD is a fully integrated, professional, multi touch 4K/2K LED LCD with amazing performance and stunning visuals.

TRIUMPH BOARD 84" MULTI Touch LED LCD is an effective presentations tool for showing lessons or presentations interactively in any classroom and meeting room. The IR LED optical technology allows six finger touch, up to six users to write and draw simultaneously using fingers, stylus or even a pointer.

The optional built-in MINI PC with incorporated Intel® Core™ i5 and i7 Processors and Microsoft® Windows® 8.1 Pro (OEM) with a selection of language options and preinstalled applications, delivering top-of-the-line performance for a zero-compromise experience.

A wide range of accessories such as LiftBoxes or mobile stands makes a perfect solution!

## **Features**

- Multi-Touch (6 Touch Input)
- 4K/2K resolution (3840 x 2160)
- Android system
- · Optional Build in MINI PC
- · Optional LiftBoxes and Stands
- TRIUMPH CLOUD the online annotation software with cloud data storage
- TB Comenius Lite the instant desktop annotation software
- Display Note the collaboration software (Cloud)

**Touch System** 

- MyScript Stylus the handwriting recognition software for easy and keyboard-free typing into any text field, in any application
- RM Easiteach Next Generation the comprehensive educational and teaching software

## **Specifications**

Display		
EAN:	8592580111853	
Screen Type:	TFT LCD/A Standard/LED backlight	
Resolution:	ULTRA HD (3840 x 2160 px)	
Display Area:	1860,48 (H) x 1046,52 mm (V)	
Display Color:	1,07 B (10 - bit)	
Diagonal size:	2134,61 mm	
Brightness:	350 cd/m2	
Contrast:	1600 : 1	
Response Time:	5 ms	
Refreshing Frequency:	120 Hz	
View Angle:	178/178 (H/V)	
Service Life:	50,000 hrs	
Mount System:	VESA 600 x 600 (Optional)	
Outline Dimension:	2005 x 1191 x 123 mm	
Package Dimension:	2170 x 1460 x 320 mm	
Net/Gross weight:	118/148 kg	
Ambient Conditions		
Operation Temperature:	0°- 40°C	

10 - 90% RH -10° - 60°C

10 - 95% RH

Touch Input:	6 Touch Input		
Sensing Type:	Infrared Transmission (multi-touch)		
Response Time:	< 20 ms (typ)		
Scan Frequency:	200 Hz		
Output Coordinates:	32767 x 32767		
Communication Mode:	Full-speed USB		
Writing Facility:	Any Opaque Object that > ø 5 mm		
Writing Screen:	Mohs hardness of 7		
Life Time:	> 80 000 hours		
PC System: Sound System	PC6A/PC7A (Optional)		
Power Amplify:	2 x 15 W		
Number of Sound Box:	2		
Sound:	Surround		
Power			
Power Requirements:	100~240 V AC 50/60 Hz		
Overall Power Consum	ption: < 500 W		
Standby Power Consur	nption: < 0,5 W		
	•		

inputs and Outputs		
HDMI IN:	4*	
VGA-OUT:	1	
Coax OUT:	1	
AUDIO OUT:	3	
Audio IN:	3	
VGA IN:	1	
USB 3.0:	1	
USB 2.0:	1	
Touch OUT:	1	
LAN (RJ45):	1	
RS 232:	1	
AC IN:	1	
Power:	1	
CVBS:	1	
R/L (CVBS):	1	

Inputs and Outputs

\*HDMI: 1x HDMI 4K 1x HDMI MHL 2x HDMI

Operation Humidity:

Storage Temperature: Storage Humidity:



